## NSN 3020-00-174-5621

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-174-5621

Body Style:
Plain, solid
Pitch Diameter:
3.1250 inches
Teeth Quantity:
25
Bore Style:
W/ keyway both ends
Hardness Rating:
30.0 rockwell c and 50.0 rockwell c
Outside Diameter:
3.375 inches
Nominallength:
0.710 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.400 inches first end
Face Width:
0.250 inches
Bore Diameter:
0.499 inches both ends
Keyway Width:
0.125 inches both ends and 0.124 inches both ends and 0.125 inches both ends and 0.124 inches both ends
Distance From Bore Center To Keyway Bottom:
0.323 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
1.000 inches second end
End Length:
0.030 inches first end
End Diameter:
0.810 inches first end
First Step Length:
0.370 inches first end
First Step Diameter:
1.000 inches first end
Material:

Steel

## NSN 3020-00-174-5621

Spur Gear - Page 2 of 2



Material Specification:
Mil-s-890, alloy 3 military specification single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-s-890 spec.

Mil-std (military Standard):

A27300