NSN 3020-00-174-7637

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-174-7637 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 3.9990 inches and 4.0000 inches **Teeth Quantity:** 128 **Bore Style:** W/counterbore both ends **Backlash Designation:** Grade b **Mounting Hole Type And Quantity:** 3 countersunk axially through body, first end **Outside Diameter:** 4.061 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees Face Width: 0.188 inches **Bore Diameter:** 0.753 inches both ends **Counterbore Depth:** 0.062 inches first end **Counterbore Diameter:** 1.531 inches first end **Precision Classification:** Quality number 10 or quality number 11 **Mounting Hole Diameter:** 0.120 inches axially through body, first end **Bolt Hole Circle Diameter:** 1.125 inches axially through body, first end Material: Plastic phenolic **Material Specification:** Mil-p-15035, type fbe military specification single material response **Style Designator:** Hubless Shelf Life:

N/a

NSN 3020-00-174-7637

Spur Gear - Page 2 of 2



	• -		
In	ıŧ	()t	Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-p-15035 spec.