NSN 3020-00-175-5301

Internal Gear - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3020-00-175-5301

Body Style:
Plain, solid
Pitch Diameter:
Between 3.7500 inches and 3.7510 inches
Teeth Quantity:
300
Backlash Designation:
Grade a
Outside Diameter:
4.3750 inches
Nominallength:
0.188 inches
Teeth Type:
Spur
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Precision Classification:
Quality number 11
Materials
Material:
Steel comp 303
Steel comp 303
Steel comp 303 Material Specification:
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment:
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification:
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response Style Designator:
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response Style Designator: Plain ring
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response Style Designator: Plain ring Shelf Life:
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response Style Designator: Plain ring Shelf Life: N/a
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response Style Designator: Plain ring Shelf Life: N/a
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response Style Designator: Plain ring Shelf Life: N/a Unit Of Measure:
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response Style Designator: Plain ring Shelf Life: N/a Unit Of Measure: Demilitarization:
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response Style Designator: Plain ring Shelf Life: N/a Unit Of Measure: Demilitarization: No
Steel comp 303 Material Specification: Qq-s-764 cond a type 303 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response Style Designator: Plain ring Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: