NSN 3020-00-175-7727

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-175-7727 **Pitch Diameter:** Between 1.6656 inches and 1.6666 inches **Teeth Quantity:** 160 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Outside Diameter:** 1.686 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.344 inches first end **Face Width:** 0.124 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 10 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t351 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** Protruding hub Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 3020-00-175-7727

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.