# NSN 3020-00-178-0052

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-178-0052

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.2917 inches **Teeth Quantity:** 35 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Hardness Rating: 28.0 rockwell c and 32.0 rockwell c Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 0.308 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.160 inches first end Face Width: 0.050 inches **Bore Diameter:** 0.094 inches both ends Hub Style Designator: Pinned second end **Hub Diameter:** 0.250 inches second end End Length: 0.140 inches first end **Precision Classification:** Quality number 10 End Diameter: 0.187 inches first end First Step Length: 0.020 inches first end

# NSN 3020-00-178-0052

Spur Gear - Page 2 of 2



### First Step Diameter:

0.250 inches first end

#### Material:

Steel comp 416

#### Material Specification:

Qq-s-764, type 416 cond h federal specification single material response

### Style Designator:

Protruding hubs

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A27300