## NSN 3020-00-178-0063

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-178-0063

Body Style:			
Plain, solid			
Attachment Method:			
Mounting hole			
Pitch Diameter:			
0.4000 inches			
Teeth Quantity:			
32			
Bore Style:			
Plain both ends			
Backlash Designation:			
Grade c			
Mounting Hole Thread Series Designator:			
Unc transversely through hub, first end			
Mounting Hole Thread Size:			
0.086 inches transversely through hub, first end			
Mounting Hole Type And Quantity:			
2 threaded transversely through hub, first end			
Outside Diameter:			
0.424 inches			
Tooth Form:			
Standard			
Pressure Angle:			
20.0000 degrees			
Distance Between Body Face And Protruding Hub End:			
0.110 inches first end			
Face Width:			
0.040 inches			
Bore Diameter:			
0.094 inches both ends			
Hub Style Designator:			
Pinned first end			
Hub Diameter:			
0.350 inches first end			
Precision Classification:			
Quality number 9			
Material:			
Aluminum alloy 2024			
Material Specification:			
Qq-a-225/6, t4 federal specification single material response			
Surface Treatment			

Anodize

## NSN 3020-00-178-0063

Spur Gear - Page 2 of 2



Surface	<b>Treatment</b>	Specification:
---------	------------------	----------------

Mil-a-8625, type 1, class 1 military specification single treatment response

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.