NSN 3020-00-181-2779



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-181-2779 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.4355 inches and 0.4375 inches **Teeth Quantity:** 28 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.070 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.466 inches Nominallength: 0.234 inches **Tooth Form:** Stub **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.010 inches second end **Face Width:** 0.083 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Plain both ends

Plain both ends

Hub Diameter:

0.280 inches second end

Material:

Copper alloy 377

Material Specification:

Qq-b-626, comp 21 federal specification single material response

Surface Treatment:

Cadmium and chromate

NSN 3020-00-181-2779

Spur Gear - Page 2 of 2



•		
StVID	l Jacian	ator.
OLYIC	Design	atoi.

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300