## NSN 3020-00-184-9330



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-184-9330 **Body Style:** Webbed, with lightening holes **Spline Quantity:** 24 both ends Pitch Diameter: 13.3333 inches **Teeth Quantity:** 80 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 2.4000 inches both ends **Hardness Rating:** 58.0 rockwell c and 62.0 rockwell c teeth **Outside Diameter:** 13.538 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.633 inches first end **Face Width:** 1.255 inches **Bore Diameter:** 2.508 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 3.230 inches first end **Special Features:** Counterbore first end, dia. 2.550 in., depth 0.440 in. Material: Steel comp 4620h or steel comp 8617h or steel comp 8620h **Material Specification:** Mil-s-13048 military specification single material response **Style Designator:** Protruding hubs Shelf Life: N/a

**Unit Of Measure:** 

## NSN 3020-00-184-9330

Spur Gear - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-s-13048 spec.