## NSN 3020-00-185-6852

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-185-6852

Body Style:
Webbed, offset, solid
Attachment Method:
Mounting hole
Pitch Diameter:
11.4000 inches
Teeth Quantity:
57
Bore Style:
W/counterbore both ends
Mounting Hole Thread Series Designator:
Unf axially through body, first end
Hardness Rating:
58.0 rockwell c and 62.0 rockwell c teeth
Mounting Hole Thread Size:
0.500 inches axially through body, first end
Mounting Hole Type And Quantity:
4 plain axially through body, first end and 12 threaded axially through body, first end
Outside Diameter:
11.765 inches
Tooth Form:
Standard
Pressure Angle:
25.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.685 inches first end
Face Width:
1.500 inches
Bore Diameter:
4.134 inches both ends
Counterbore Depth:
1.183 inches second end
Counterbore Diameter:
4.440 inches second end
Hub Style Designator:
Plain both ends
Hub Diameter:
4.560 inches first end
Mounting Hole Diameter:
0.870 inches axially through body, first end

Material:

Steel comp 3130h or steel comp 4320h or steel comp 4621h

## NSN 3020-00-185-6852

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-s-13048 spec.



Material Specification:
Mil-s-13048 military specification single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300