NSN 3020-00-187-7859

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-187-785
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.4286 inches
Teeth Quantity:
20
Bore Style:
Plain both ends
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Mounting Hole Type And Quantity:
4 plain axially through flange
Outside Diameter:
1.570 inches
Tooth Form:
Standard
Flange Diameter:
3.875 inches
Pressure Angle:
25.0000 degrees
Flange Thickness:
0.280 inches
Face Width:
0.260 inches
Bore Diameter:
0.975 inches both ends
Distance Between Outer Body Face And Inner Flange Face:
0.505 inches
Hub Style Designator:
Plain first end
Hub Diameter:
1.215 inches between body and flange
Precision Classification:
Quality number 10 or quality number 11
Mounting Hole Diameter:
0.278 inches axially through flange
Bolt Hole Circle Diameter:
2.500 inches axially through flange
Material:
Steel comp 4340

NSN 3020-00-187-7859

Spur Gear - Page 2 of 2



Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Phosphate

Style Designator:

Hubless

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5000 spec.