## NSN 3020-00-190-4956

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-190-4956

Body Style:
Plain, solid
Pitch Diameter:
Between 0.5615 inches and 0.5625 inches
Teeth Quantity:
36
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
0.593 inches
Nominallength:
0.312 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.218 inches first end
Face Width:
0.094 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.375 inches first end
Precision Classification:
Quality number 10
Special Features:
Mtg holes 90 degs apart
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize hub
Surface Treatment Specification:
Mil-a-8625, type 1, class 1 military specification single treatment response hub
Style Designator:
Protruding hub

## NSN 3020-00-190-4956

Spur Gear - Page 2 of 2



Furnished Items And Quantity:
1 setscrew
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):

Mil-a-8625 spec.