NSN 3020-00-193-1220

Sprocket Wheel - Page 1 of 2





Outside Diameter: 1.070 inches **Overall Length:** Between 0.445 inches and 0.455 inches **Bore Diameter:** Between 0.443 inches and 0.445 inches Bore Length: Between 0.445 inches and 0.455 inches **Pitch Diameter:** 0.921 inches Face Width: 0.110 inches **Design Form:** Plain Bore Type: Straight **Counterbore Feature:** Not included **Keying Facility:** Not included Lightening Hole: Not included **Protruding Hub Characteristic:** Plain Belt/chain/film Size For Which Designed: Roller chain **Roller Chain Pitch Type For Which Designed:** Single pitch **Teeth Row Quantity:** 1 **Teeth Quantity Per Row:** 9 Asa Standard Chain Number: 88 Hardness Rating Test Method: Not rated **Bore Bearing:** Not included Hub External Keyway: Not included **Tooth Pitch:** 0.315 inches

NSN 3020-00-193-1220

Sprocket Wheel - Page 2 of 2



Hub End Outside Diameter And Location:

0.583 inches aa end and 0.593 inches aa end and 0.583 inches bb end and 0.593 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.170 inches aa end and 0.170 inches bb end

Material:

Steel, an-s-14

Material:

Steel, an-s-14

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T353-c