NSN 3020-00-195-5834

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-195-5834

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.8750 inches
Teeth Quantity:
42
Bore Style:
Partial first end
Mounting Hole Type And Quantity:
2 plain transversely through hub, first end
Outside Diameter:
0.917 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.172 inches first end
Face Width:
0.109 inches
Bore Diameter:
0.125 inches both ends
Bore Depth:
0.2812 inches first end
Hub Style Designator:
Plain second end
Hub Diameter:
0.281 inches second end
First Groove Width:
0.141 inches first end
First Groove Diameter:
0.531 inches first end
Distance From End To First Groove:
0.031 inches first end
Mounting Hole Diameter:
0.035 inches transversely through hub, first end
Special Features:
Integral actuator ring, counterbore 0.4375 in. Diameter by 0.100 in. Deep 1st end; grooved 2nd end
Material:
Stainless steel

NSN 3020-00-195-5834

Spur Gear - Page 2 of 2



_	•		_			
ن	ırfa	\sim	Irο	o+n	20r	٠.
υı	ai ia	uc.	116	аш	161	IL.

Passivate

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300