NSN 3020-00-195-6027



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-195-6027 **Attachment Method:** Mounting hole **Pitch Diameter:** Between 3.9052 inches and 3.9062 inches **Teeth Quantity:** 125 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 3.968 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.240 inches first end **Body Recess Depth:** 0.031 inches second end **Face Width:** 0.187 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.500 inches first end Material: Steel comp 303 **Material Specification:** Qq-s-763, class303 federal specification single material response

Surface Treatment: Passivate Style Designator: Protruding hub, recessed body **Furnished Items And Quantity:** 1 setscrew

NSN 3020-00-195-6027

Spur Antibacklash Gear - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300