## NSN 3020-00-204-3007



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-204-3007 **Body Style:** Spoked **Attachment Method:** Mounting hole Pitch Diameter: 10.0630 inches **Teeth Quantity:** 160 **Bore Style:** W/ keyway both ends **Mounting Hole Thread Series Designator:** Unc axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 18 axially through hub, first end **Mounting Hole Thread Size:** 0.313 inches axially through hub, first end **Mounting Hole Type And Quantity:** 3 threaded axially through hub, first end **Outside Diameter:** 10.122 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.282 inches first end **Face Width:** 0.813 inches **Bore Diameter:** 3.143 inches both ends **Keyway Width:** 0.249 inches both ends **Distance From Bore Center To Keyway Bottom:** 1.697 inches both ends

**Hub Style Designator:** 

Plain first end

**Hub Diameter:** 

4.625 inches first end

**Bolt Hole Circle Diameter:** 

3.875 inches axially through hub, first end

Material:

Copper alloy

## NSN 3020-00-204-3007

Spur Gear - Page 2 of 2



Material Specification:
Mil-m-16576, grade a military specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

140

Fiig:

A27300

Mil-std (military Standard):

Mil-m-16576 spec.