NSN 3020-00-204-3007

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-204-3007

Body Style: Spoked **Attachment Method:** Mounting hole **Pitch Diameter:** 10.0630 inches **Teeth Quantity:** 160 **Bore Style:** W/ keyway both ends **Mounting Hole Thread Series Designator:** Unc axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 18 axially through hub, first end Mounting Hole Thread Size: 0.313 inches axially through hub, first end Mounting Hole Type And Quantity: 3 threaded axially through hub, first end **Outside Diameter:** 10.122 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.282 inches first end Face Width: 0.813 inches **Bore Diameter:** 3.143 inches both ends **Keyway Width:** 0.249 inches both ends Distance From Bore Center To Keyway Bottom: 1.697 inches both ends Hub Style Designator: Plain first end Hub Diameter: 4.625 inches first end **Bolt Hole Circle Diameter:** 3.875 inches axially through hub, first end Material: Copper alloy

NSN 3020-00-204-3007

Spur Gear - Page 2 of 2



Material Specification:

Mil-m-16576, grade a military specification single material response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-m-16576 spec.