NSN 3020-00-204-9504

Attachment Method:

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-204-9504

Clamp
Pitch Diameter:
Between 1.3115 inches and 1.3125 inches
Teeth Quantity:
84
Bore Style:
Plain both ends
Outside Diameter:
1.343 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.313 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.313 inches first end
Clamping Surface Length:
0.250 inches first end
Precision Classification:
Quality number 10
Special Features:
For navy nuclear propulsion plant products only
Material:
Stainless steel spring
Material Specification:
Qq-s-764, cond a federal specification single material response hub
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response second gear
Style Designator:
Protruding hub
Reference Number Differentiating Characteristics:
As differentiated by free from mercury contamination

NSN 3020-00-204-9504

Spur Antibacklash Gear - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Shelf Life:

Mil-std (military Standard):

Mil-a-8625 spec.