## NSN 3020-00-204-9512

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-204-9512 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.6657 inches and 0.6667 inches **Teeth Quantity:** 64 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Mounting Hole Type And Quantity:** 2 plain transversely through hub, first end **Outside Diameter:** 0.688 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.234 inches first end **Face Width:** 0.094 inches **Bore Diameter:** 0.188 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.312 inches first end **Precision Classification:** Quality number 10 **Mounting Hole Diameter:** 0.062 inches transversely through hub, first end Material: Copper alloy 360 **Material Specification:** Qq-b-626, 1/2 hard federal specification single material response **Style Designator:** Protruding hub Shelf Life:

N/a

## **NSN 3020-00-204-9512** Spur Gear - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A27300