## NSN 3020-00-211-2430

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-211-2430

Attachment Method:		
Mounting hole		
Teeth Quantity:		
84		
Bore Style:		
Plain both ends		
Pitch Radius:		
4.3750 inches		
Backlash Designation:		
Grade d		
Mounting Hole Thread Series Designator:		
Unc transversely through hub, first end		
Mounting Hole Thready Qty Per Inch (tpi):		
20 transversely through hub, first end		
Mounting Hole Thread Size:		
0.250 inches transversely through hub, first end		
Mounting Hole Type And Quantity:		
1 threaded transversely through hub, first end		
Nominallength:		
1.000 inches		
Tooth Form:		
Standard		
Pressure Angle:		
20.0000 degrees		
Distance Between Body Face And Protruding Hub End:		
0.6250 inches first end		
Face Width:		
0.375 inches		
Bore Diameter:		
1.250 inches both ends		
Hub Style Designator:		
Pinned first end		
Hub Diameter:		
2.2500 inches first end		
Outside Radius:		
4.3940 inches		
Precision Classification:		
Quality number 9		
Arc Length:		
5.2500 inches		
Material:		

Aluminum alloy 2024

## NSN 3020-00-211-2430

Spur Gear Sector - Page 2 of 2



Surface	Treatm	ent:
---------	--------	------

Anodize

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300