## NSN 3020-00-211-3333

Spur Gear - Page 1 of 2

**Body Style:** 





## Spoked **Attachment Method:** Mounting hole **Pitch Diameter:** 3.0000 inches **Teeth Quantity:** 144 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end Mounting Hole Thread Size: 0.112 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 3.042 inches Nominallength: 0.437 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.313 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.120 inches both ends Hub Style Designator: Plain second end **Hub Diameter:** 0.625 inches second end Material: Copper alloy Style Designator: One protruding hub, one flush hub **Furnished Items And Quantity:** 1 lubricant impregnated bearing

## NSN 3020-00-211-3333

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

