NSN 3020-00-211-6182

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-211-6182

| Body Style: |
|---|
| |
| Plain, solid |
| Attachment Method: |
| Clamp Ritch Diameters |
| Pitch Diameter: |
| 0.8000 inches |
| Teeth Quantity: |
| 96 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 0.814 inches |
| Nominallength: |
| 0.391 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.297 inches first end |
| Face Width: |
| 0.094 inches |
| Bore Diameter: |
| 0.188 inches both ends |
| Hub Style Designator: |
| Split first end |
| Hub Diameter: |
| 0.249 inches first end |
| Clamping Surface Length: |
| 0.265 inches first end |
| Precision Classification: |
| Quality number 10 or quality number 11 |
| Material: |
| Aluminum alloy 2024 and aluminum alloy 6061 |
| Material Specification: |
| Qq-a-225/6, t4 federal specification single material response and qq-a-225/8, t6 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 1 military specification single treatment response |
| Style Designator: |

Protruding hub

NSN 3020-00-211-6182

Spur Gear - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.