NSN 3020-00-215-4032



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-215-4032 **Outside Diameter:** 3.109 inches **Overall Length:** 1.141 inches **Keyway Width:** 0.156 inches **Bore Diameter:** 1.000 inches **Bore Length:** 1.141 inches Distance From Center Of Bore To Bottom Of Keyway: 0.578 inches **Drilled Hole Diameter:** 0.189 inches **Pitch Diameter:** 2.809 inches **Securing Hole Quantity:** Face Width: 0.165 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Metallic Hardness Rating And Location:** 45.0 rockwell c body and 63.0 rockwell c body **Counterbore Feature:** Not included **Hole Location:** 90 degrees from keyway **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Drilled hole **Lightening Hole:**

Protruding Hub Characteristic:

Plain

Not included

NSN 3020-00-215-4032 Sprocket Wheel - Page 2 of 2



Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
14
Asa Standard Chain Number:
50-1
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 45.0 rockwell c and 63.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.630 inches
Hub End Outside Diameter And Location:
1.750 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.986 inches aa end
Material:
Steel
Material:
Steel
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c