# NSN 3020-00-216-6625

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-216-6625

# **Body Style:**

Webbed, offset, solid

# Spline Quantity:

23 both ends

# Pitch Diameter:

2.3529 inches

# **Teeth Quantity:**

18

#### Bore Style:

Involute spline both ends

#### Spline Pitch Diameter:

2.3529 inches both ends

#### Hardness Rating:

30.0 rockwell c and 35.0 rockwell c

# **Outside Diameter:**

2.587 inches

# Nominallength:

0.880 inches

# Tooth Form:

Special

# Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.200 inches first end

### Face Width:

0.560 inches

#### **Bore Diameter:**

0.725 inches both ends

# Hub Style Designator:

Plain second end

#### Hub Diameter:

1.060 inches second end

#### End Length:

0.080 inches first end

# **Precision Classification:**

Quality number 9

# End Diameter:

1.062 inches first end

### First Step Length:

0.120 inches first end

# First Step Diameter:

1.790 inches first end

# NSN 3020-00-216-6625

Spur Gear - Page 2 of 2



Material:

Steel comp 4140

#### **Material Specification:**

Qq-s-624 federal specification single material response

### Surface Treatment:

Phosphate manganese or phosphate zinc

# Surface Treatment Specification:

Mil-std-171 cl3 military standard single treatment response

### Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A27300

#### Mil-std (military Standard):

Mil-std-171 spec.