## NSN 3020-00-217-0527

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-217-0527 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.0000 inches **Teeth Quantity:** 48 **Bore Style:** Plain both ends **Features Provided:** Casehardened **Mounting Hole Type And Quantity:** 2 countersunk axially through body, first end **Outside Diameter:** 1.042 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.016 inches second end **Face Width:** 0.094 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.375 inches second end **End Length:** 0.195 inches first end **End Diameter:** 0.500 inches first end First Step Length: 0.061 inches first end First Step Diameter:

0.750 inches first end **Mounting Hole Diameter:** 0.094 inches axially through body, first end **Bolt Hole Circle Diameter:** 0.625 inches axially through body, first end

## **NSN 3020-00-217-0527** Spur Gear - Page 2 of 2

Fiig: A27300



Special Features:
1st end hub end has setscrew hole and is spot drilled for pinning
Material:
Steel
Material Specification:
66 federal standard single material response and aisi 1211/sae 1111 assn standard single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No