

View Online at <https://aerobasegroup.com/nsn/3020-00-217-5707>

Groove Depth:

0.600 inches

Groove Width:

0.500 inches

Outside Diameter:

5.377 inches

Bolt Circle Diameter:

3.250 inches

Keyway Width:

0.250 inches

Thread Size:

5/16-18

Bore Diameter:

1.180 inches

Bore Length:

0.939 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.720 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

5.027 inches

Flange Outside Diameter:

7.360 inches

Securing Hole Quantity:

2

Material And Location:

Iron, cast

Face Width:

2.727 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Hole Location:

Thru pulley body

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

4l

Bore Feature:

Included

Securing Location:

Bb end

Hub End Outside Diameter And Location:

2.043 inches aa end and 2.043 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.905 inches aa end and 0.883 inches bb end

Special Features:

Pulley has weighted 7.365 in.D/a flange at aa end.

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T353-a