NSN 3020-00-220-3718

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-220-3718 **Attachment Method:** Clamp **Pitch Diameter:** Between 2.2907 inches and 2.2917 inches **Teeth Quantity:** 220 **Bore Style:** Plain both ends **Backlash Designation:** Grade e **Outside Diameter:** 2.312 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.221 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.090 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.185 inches first end **Clamping Surface Length:** 0.190 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303 hub **Material Specification:** Qq-s-764, cona a federal specification single material response hub **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response hub **Style Designator:** Protruding hub

N/a

Shelf Life:

NSN 3020-00-220-3718

Spur Antibacklash Gear - Page 2 of 2



	• -		
In	ıŧ	()t	Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.