# NSN 3020-00-220-5741

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-220-5741

Outside Diameter:
1.228 inches
Overall Length:

0.500 inches

Thread Size:

6-32

#### **Bore Diameter:**

Between 0.5004 inches and 0.5009 inches

#### **Bore Length:**

0.500 inches

**Pitch Diameter:** 

1.177 inches

#### Securing Hole Quantity:

2

### Face Width:

0.062 inches

#### **Design Form:**

Plain

#### Bore Type:

Straight

#### Counterbore Feature:

Not included

#### Hole Location:

Located on hub portion 180 degree apart

#### **Keying Facility:**

Not included

#### **Securing Method:**

Threaded hole

#### Lightening Hole:

Not included

#### **Protruding Hub Characteristic:**

Plain

# Securing Location:

Aa end

# Belt/chain/film Size For Which Designed:

Roller chain

# Roller Chain Pitch Type For Which Designed:

Single pitch

# Teeth Row Quantity:

1

# Teeth Quantity Per Row:

25

# **NSN 3020-00-220-5741** Sprocket Wheel - Page 2 of 2



Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.148 inches
Hub End Outside Diameter And Location:
0.980 inches aa end and 0.630 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
0.223 inches aa end and 0.187 inches bb end
Material:
Steel, mil-s-7720, comp 303s, cond a
Material:
Steel comp 303
Material Specification:
Mil-s-7720, comp 303s, cond a military specification single material response
Surface Treatment:
Paint
Style Designator:
Plain
Surface Treatment:
Painted
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-с
Mil-std (military Standard):
Mil-s-7720 spec.