
NSN 3020-00-223-3351

Spur Gear - Page 1 of 2





Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 2.0000 inches **Teeth Quantity:** 144 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 40 axially through body, first end Mounting Hole Thread Size: 0.112 inches axially through body, first end Mounting Hole Type And Quantity: 3 threaded axially through body, first end **Outside Diameter:** 2.026 inches Nominallength: 0.370 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.240 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.187 inches both ends Hub Style Designator: Split first end **Hub Diameter:** 0.249 inches first end **Clamping Surface Length:** 0.245 inches first end **Precision Classification:** Quality number 12 **Bolt Hole Circle Diameter:**

0.112 inches axially through body, first end

NSN 3020-00-223-3351

Spur Gear - Page 2 of 2



Material:

Aluminum alloy 2024

Material Specification:

Qq-a-225/6, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.