NSN 3020-00-225-6968



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-225-6968 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.6041 inches **Teeth Quantity:** 58 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.625 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.156 inches first end **Face Width:** 0.094 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.312 inches first end **Precision Classification:** Ultra precision class 1 Material: Steel comp 303 **Material Specification:** Mil-s-7720 military specification single material response

Surface Treatment: Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 3020-00-225-6968

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Furnished Items And Quantity:
2 setscrew
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.