NSN 3020-00-225-6970

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-225-6970 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.9375 inches **Teeth Quantity:** 90 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.958 inches Nominallength: 0.218 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.156 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.312 inches first end **Precision Classification:** Ultra precision class 1 Material: Steel comp 303

Material Specification:

Mil-s-7720 military specification single material response

NSN 3020-00-225-6970

Spur Gear - Page 2 of 2

Mil-s-7720 spec.



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):