
## NSN 3020-00-225-6971

Spur Gear - Page 1 of 2





**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.0417 inches **Teeth Quantity:** 100 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 1.063 inches Nominallength: 0.281 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.156 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.090 inches both ends Hub Style Designator: Pinned first end **Hub Diameter:** 0.312 inches first end **Precision Classification:** Quality number 9 Material: Steel comp 303 **Material Specification:** 

Mil-s-7720 military specification single material response

## NSN 3020-00-225-6971

Spur Gear - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.