NSN 3020-00-226-1137

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-226-1137 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 2.4990 inches and 2.5000 inches **Teeth Quantity:** 160 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 2.529 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.375 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.275 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Steel comp 303 hub

Material Specification:

Qq-a-225/6, t4 federal specification single material response teeth

NSN 3020-00-226-1137

Spur Gear - Page 2 of 2



Passivate hub
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.

Surface Treatment: