
# NSN 3020-00-229-6940

Spur Gear - Page 1 of 2



## **Body Style:**

Plain, solid

## **Attachment Method:**

Clamp

# **Pitch Diameter:**

Between 1.7493 inches and 1.7500 inches

# **Teeth Quantity:**

126

Bore Style:

Plain both ends

# **Outside Diameter:**

0.281 inches

#### Nominallength:

0.406 inches

#### **Tooth Form:**

Standard

# Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.281 inches first end

# Face Width:

0.125 inches

# Bore Diameter:

0.187 inches both ends

#### Hub Style Designator:

Split first end

## Hub Diameter:

0.250 inches first end

# **Clamping Surface Length:**

0.250 inches first end

#### **Special Features:**

Hub is also stepped, 0.312 in.Dia, 0.031 in.Lg

#### Material:

Steel comp 303

# Material Specification:

Mil-s-7720, comp 303s military specification single material response

# Surface Treatment:

Passivate

# Style Designator:

Protruding hub

# Shelf Life:

N/a



# NSN 3020-00-229-6940

Spur Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.

