NSN 3020-00-229-9499

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-229-9499 **Attachment Method:** Clamp Pitch Diameter: 1.6458 inches **Teeth Quantity:** 79 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Outside Diameter:** 1.6875 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.313 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.313 inches first end **Clamping Surface Length:** 0.250 inches first end **Precision Classification:** Quality number 10 **Special Features:** One plain hole 0.064 in. Diameter through body on 0.600 in. Bolt circledia Material: Stainless steel hub **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response teeth **Style Designator:** Protruding hub

N/a

Shelf Life:

NSN 3020-00-229-9499

Spur Antibacklash Gear - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.