NSN 3020-00-230-1562

Spur Gear-slip Clutch - Page 1 of 2

Attachment Method:



View Online at https://aerobasegroup.com/nsn/3020-00-230-1562

Mounting hole					
Pitch Diameter:					
2.6666 inches					
Torque Capacity:					
10.00 inch-ounces					
Teeth Quantity:					
192					
Bore Style:					
Plain both ends					
Mounting Hole Thread Series Designator:					
Unc transversely through hub, first end					
Mounting Hole Thread Size:					
0.138 inches transversely through hub, first end					
Mounting Hole Type And Quantity:					
1 threaded transversely through hub, first end					
Outside Diameter:					
2.6944 inches					
Nominallength:					
0.803 inches					
Tooth Form:					
Standard					
Pressure Angle:					
20.0000 degrees					
Distance Between Body Face And Protruding Hub End:					
0.263 inches first end					
Face Width:					
0.125 inches					
Bore Diameter:					
0.187 inches both ends					
Distance Between Face Edge And Body End:					
0.415 inches					
Precision Classification:					
Quality number 10 or quality number 11					
Special Features:					
Clutch spring must be altered					
Material:					
Stainless steel					
Surface Treatment:					
Passivate hub					
Style Designator:					
Fixed torque, spring washer loaded					

NSN 3020-00-230-1562

Spur Gear-slip Clutch - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300