NSN 3020-00-230-1562

Spur Gear-slip Clutch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-230-1562

| Attachment Method: |
|---|
| Mounting hole |
| Pitch Diameter: |
| 2.6666 inches |
| Torque Capacity: |
| 10.00 inch-ounces |
| Teeth Quantity: |
| 192 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Thread Series Designator: |
| Unc transversely through hub, first end |
| Mounting Hole Thread Size: |
| 0.138 inches transversely through hub, first end |
| Mounting Hole Type And Quantity: |
| 1 threaded transversely through hub, first end |
| Outside Diameter: |
| 2.6944 inches |
| Nominallength: |
| 0.803 inches |
| Tooth Form: |
| Standard |
| Brocouro Anglo |
| Pressure Angle: |
| 20.0000 degrees |
| - |
| 20.0000 degrees |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: 0.415 inches Precision Classification: |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: 0.415 inches Precision Classification: Quality number 10 or quality number 11 |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: 0.415 inches Precision Classification: Quality number 10 or quality number 11 Special Features: |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: 0.415 inches Precision Classification: Quality number 10 or quality number 11 |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: 0.415 inches Precision Classification: Quality number 10 or quality number 11 Special Features: Clutch spring must be altered |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: 0.415 inches Precision Classification: Quality number 10 or quality number 11 Special Features: Clutch spring must be altered Material: |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: 0.415 inches Precision Classification: Quality number 10 or quality number 11 Special Features: Clutch spring must be altered Material: Stainless steel Surface Treatment: |
| 20.000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: 0.415 inches Precision Classification: Quality number 10 or quality number 11 Special Features: Clutch spring must be altered Material: Stainless steel Surface Treatment: Passivate hub |
| 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.263 inches first end Face Width: 0.125 inches Bore Diameter: 0.187 inches both ends Distance Between Face Edge And Body End: 0.415 inches Precision Classification: Quality number 10 or quality number 11 Special Features: Clutch spring must be altered Material: Stainless steel Surface Treatment: |

NSN 3020-00-230-1562

Spur Gear-slip Clutch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

