NSN 3020-00-231-2300

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-231-2300

| Body Style: |
|---|
| Spoked |
| Pitch Diameter: |
| 3.7500 inches |
| Teeth Quantity: |
| 120 |
| Bore Style: |
| W/ keyway both ends |
| Outside Diameter: |
| 3.812 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.440 inches first end |
| Face Width: |
| 0.188 inches |
| Bore Diameter: |
| 0.375 inches both ends |
| Keyway Width: |
| 0.094 inches both ends |
| Distance From Bore Center To Keyway Bottom: |
| 0.240 inches both ends |
| Hub Style Designator: |
| 1 step first end |
| End Length: |
| 0.065 inches first end |
| Precision Classification: |
| Quality number 10 or quality number 11 |
| End Diameter: |
| 0.469 inches first end |
| First Step Length: |
| 0.374 inches first end |
| First Step Diameter: |
| 0.625 inches first end |
| Material: |
| Copper alloy |
| Material Specification: |
| Qq-b-671, cl 3 federal specification single material response |
| Style Designator: |

One protruding hub, one flush hub

NSN 3020-00-231-2300

Spur Gear - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300