

View Online at <https://aerobasegroup.com/nsn/3020-00-232-6016>

Outside Diameter:

Between 8.310 inches and 8.320 inches

Overall Length:

1.172 inches

Keyway Width:

Between 0.313 inches and 0.319 inches

Thread Size:

5/16 in.-18

Bore Diameter:

Between 1.249 inches and 1.251 inches

Bore Length:

1.016 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.795 inches and 0.805 inches

Pitch Diameter:

7.966 inches

Securing Hole Quantity:

1

Face Width:

0.750 inches

Design Form:

Webbed

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

Located on top of keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Lightening Hole:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

1

Teeth Quantity Per Row:

40

Asa Standard Chain Number:

50

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

0.625 inches

Hub End Outside Diameter And Location:

2.750 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.422 inches aa end and 0.156 inches bb end

Material:

Steel, qq-s-681, comp 65-35, cond a

Material:

Steel, qq-s-681, comp 65-35, cond a

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-c