

View Online at <https://aerobasegroup.com/nsn/3020-00-232-6016>

**Outside Diameter:**

Between 8.310 inches and 8.320 inches

**Overall Length:**

1.172 inches

**Keyway Width:**

Between 0.313 inches and 0.319 inches

**Thread Size:**

5/16 in.-18

**Bore Diameter:**

Between 1.249 inches and 1.251 inches

**Bore Length:**

1.016 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

Between 0.795 inches and 0.805 inches

**Pitch Diameter:**

7.966 inches

**Securing Hole Quantity:**

1

**Face Width:**

0.750 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Counterbore Feature:**

Not included

**Hole Location:**

Located on top of keyway

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Lightening Hole:**

Included

**Protruding Hub Characteristic:**

Plain

**Securing Location:**

Aa end

**Belt/chain/film Size For Which Designed:**

Roller chain

**Roller Chain Pitch Type For Which Designed:**

Single pitch

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

40

**Asa Standard Chain Number:**

50

**Hardness Rating Test Method:**

Not rated

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

0.625 inches

**Hub End Outside Diameter And Location:**

2.750 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

0.422 inches aa end and 0.156 inches bb end

**Material:**

Steel, qq-s-681, comp 65-35, cond a

**Material:**

Steel, qq-s-681, comp 65-35, cond a

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-c