NSN 3020-00-233-7772

Cone Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-233-7772 **Groove Depth:** 0.690 inches **Groove Width:** 0.656 inches and 0.637 inches and 0.656 inches **Overall Length:** 2.560 inches **Bolt Circle Diameter:** 2.124 inches **Thread Size:** 0.375-16 V Groove Angle In Deg: 40.0 **Securing Hole Quantity:** Face Type: Step groove **Taper Bore Major Diameter:** 2.240 inches **Material And Location:** Aluminum alloy Face Width: 0.840 inches and 0.840 inches and 0.880 inches **Design Form:** Webbed **Bore Type: Tapered** Step Quantity: **Taper Major Diameter Location:** 8.500 inches and 6.974 inches and 4.500 inches

Aa end **Groove Quantity: Counterbore Feature:** Not included **Step Outside Diameter: Hole Location:** On pulley face **Keying Facility:** Not included **Securing Method:** Threaded hole

NSN 3020-00-233-7772

Cone Pulley - Page 2 of 2



| Split Hub Feature: |
|---|
| Not included |
| Web/spoke Relationship To Face Centerline: |
| Offset |
| Lightening Hole: |
| Not included |
| Integral Cooling Vane: |
| Not included |
| Groove Shape: |
| V |
| Standard V-belt Section Designation For Which Designed: |
| C |
| Bore Bearing: |
| Not included |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.750 inches aa end |
| V Groove Pitch Diameter: |
| 8.000 inches |
| Style Designator: |
| Webbed or spoked |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . |
| Demilitarization: |
| No |
| Fiig: |
| T353-b |
| |