## NSN 3020-00-237-1052

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-237-1052

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 0.4511 inches and 0.4521 inches
Teeth Quantity:
44
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unf transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
80 transversely through hub, first end
Mounting Hole Thread Size:
0.060 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.472 inches
Nominallength:
0.170 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.108 inches first end
Face Width:
0.062 inches
Bore Diameter:
0.090 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.300 inches first end
Precision Classification:
Quality number 10 or quality number 11
Material:
Steel comp 303
Material Specification:

Mil-s-7720, comp 303s military specification single material response

## NSN 3020-00-237-1052

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-s-7720 spec.