NSN 3020-00-238-7912

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-238-7912

Outside Diameter:

- 5.938 inches
- **Overall Length:**
- 3.500 inches

Keyway Width:

0.500 inches

Thread Size:

5/8 in.-11

Bore Diameter:

Between 1.939 inches and 1.941 inches

Bore Length:

3.500 inches

Distance From Center Of Bore To Bottom Of Keyway:

1.220 inches and 1.159 inches

Pitch Diameter:

5.350 inches

Securing Hole Quantity:

1

Face Width:

0.812 inches

Design Form:

Plain

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

Locted on hub on top of keyway at end w/deepest keyway depth

Keying Facility:

Included

Keying Facility Type:

Tapered keyway

Securing Method:

Threaded hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Securing Location:

Both ends

Belt/chain/film Size For Which Designed:

Roller chain

NSN 3020-00-238-7912

Sprocket Wheel - Page 2 of 2



Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

1

Teeth Quantity Per Row:

10

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

1.654 inches

Hub End Outside Diameter And Location:

3.500 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

1.344 inches both ends

Material:

Steel, aisi 1040 or steel, sae 1040

Material:

Steel comp 1040 or steel comp 1040

Material Specification:

Aisi 1040 assn standard 1st material response and sae 1040 assn standard 2nd material response

Quantity:

1

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T353-c