## NSN 3020-00-238-7912

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-238-7912 **Outside Diameter:** 5.938 inches **Overall Length:** 3.500 inches **Keyway Width:** 0.500 inches **Thread Size:** 5/8 in.-11 **Bore Diameter:** Between 1.939 inches and 1.941 inches **Bore Length:** 3.500 inches **Distance From Center Of Bore To Bottom Of Keyway:** 1.220 inches and 1.159 inches Pitch Diameter: 5.350 inches **Securing Hole Quantity:** Face Width: 0.812 inches **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** Locted on hub on top of keyway at end w/deepest keyway depth **Keying Facility:** Included **Keying Facility Type:** Tapered keyway **Securing Method:** Threaded hole **Lightening Hole:** Not included **Protruding Hub Characteristic:** Plain **Securing Location:** 

Both ends Belt/chain/film Size For Which Designed: Roller chain

## **NSN 3020-00-238-7912** Sprocket Wheel - Page 2 of 2



Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
10
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
1.654 inches
Hub End Outside Diameter And Location:
3.500 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
1.344 inches both ends
Material:
Steel, aisi 1040 or steel, sae 1040
Material:
Steel comp 1040 or steel comp 1040
Material Specification:
Aisi 1040 assn standard 1st material response and sae 1040 assn standard 2nd material response
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
Г353-с