NSN 3020-00-239-1067

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-239-1067

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 2.6990 inches and 2.7000 inches
Teeth Quantity:
216
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unf transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
80 transversely through hub, first end
Mounting Hole Thread Size:
0.060 inches transversely through hub, first end
Mounting Hole Type And Quantity:
4 threaded transversely through hub, first end
Outside Diameter:
2.723 inches
Nominallength:
0.156 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.031 inches both ends
Face Width:
0.094 inches
Bore Diameter:
1.670 inches both ends
Hub Style Designator:
Plain both ends
Hub Diameter:
2.644 inches both ends
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11, t6 federal specification single material response
Surface Treatment:
Anodize

NSN 3020-00-239-1067

Spur Gear - Page 2 of 2



Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.