NSN 3020-00-239-1093

Spur Gear - Page 1 of 2

Body Style: Plain, solid



View Online at https://aerobasegroup.com/nsn/3020-00-239-1093

Attachment Method:				
Mounting hole				
Pitch Diameter:				
2.4990 inches				
Teeth Quantity:				
120				
Bore Style:				
Plain both ends				
Mounting Hole Thread Series Designator:				
Unc axially through body, first end				
Mounting Hole Thread Size:				
0.1250 inches axially through body, first end				
Mounting Hole Type And Quantity:				
1 plain axially through body, first end and 1 threaded axially through body, first end				
Outside Diameter:				
2.5390 inches				
Tooth Form:				
Standard				
Pressure Angle:				
20.0000 degrees				
Distance Between Body Face And Protruding Hub End:				
0.4370 inches first end				
Face Width:				
0.1250 inches				
Bore Diameter:				
0.3760 inches both ends				
Hub Style Designator:				
Plain first end				
Hub Diameter:				
0.7190 inches first end				
Precision Classification:				
Quality number 10				
Mounting Hole Diameter:				
0.1250 inches axially through body, first end				
Special Features:				
1 0.089 in. Diameter plain hole and 1 0.138 in. Diameter threaded hole on hub for positioning				
Material:				
Steel comp 303				
Material Specification:				

Qq-s-764, , cond a-canceled federal specification single material response

NSN 3020-00-239-1093

Spur Gear - Page 2 of 2



_	•	_		
	irtac	_O Irα	aatm	ent:
J	ui iau	C 110	sauı	ICIIL.

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300