# NSN 3020-00-239-1103

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-239-1103

# **Attachment Method:**

Mounting hole

**Teeth Quantity:** 

18

# Bore Style:

Plain both ends

# **Pitch Radius:**

0.4000 inches

#### Nominallength:

0.250 inches

Tooth Form:

#### Standard

Pressure Angle:

#### 20.0000 degrees

Distance Between Body Face And Protruding Hub End:

## 0.188 inches first end

Face Width:

#### 0.062 inches

## Bore Diameter:

0.125 inches both ends

#### Hub Style Designator:

Plain second end

## Hub Diameter:

0.1870 inches second end

#### **Outside Radius:**

0.4250 inches

#### End Length:

0.079 inches first end

#### End Diameter:

0.187 inches first end

#### First Step Length:

0.109 inches first end

#### First Step Diameter:

0.312 inches first end

# Arc Length:

0.2160 inches

## **Special Features:**

Holes located hub between hub end and gear face 90 degrees apart; 2 thd holes; nc thd series; 0.086 in. Nom hole thd size; 56 thds per in.

#### ....

Material:

Steel comp 303

### Material Specification:

# NSN 3020-00-239-1103

Spur Gear Sector - Page 2 of 2



Surface Treatment:

Passivate

## Surface Treatment Specification:

Mil-std-171, finish no. 5.4.1 military standard single treatment response

# Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A27300

# Mil-std (military Standard):

Mil-std-171 spec.