NSN 3020-00-239-7628

Helical Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-239-7628

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.2304 inches
Teeth Quantity:
14
Bore Style:
W/ keyway first end
Mounting Hole Type And Quantity:
2 plain axially through body, first end
Outside Diameter:
1.4062 inches
Nominallength:
0.875 inches
Teeth Type:
Single helix
Tooth Form:
Standard
Tooth Direction:
Left
Pressure Angle:
14.5000 degrees
Helix Angle:
Helix Angle: 45.0000 degrees
45.0000 degrees
45.0000 degrees Distance Between Body Face And Protruding Hub End:
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width:
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches Bore Diameter:
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches Bore Diameter: 0.3750 inches first end
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches Bore Diameter: 0.3750 inches first end Keyway Width:
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches Bore Diameter: 0.3750 inches first end Keyway Width: 0.125 inches both ends
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches Bore Diameter: 0.3750 inches first end Keyway Width: 0.125 inches both ends Distance From Bore Center To Keyway Bottom:
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches Bore Diameter: 0.3750 inches first end Keyway Width: 0.125 inches both ends Distance From Bore Center To Keyway Bottom: 0.2500 inches first end
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches Bore Diameter: 0.3750 inches first end Keyway Width: 0.125 inches both ends Distance From Bore Center To Keyway Bottom: 0.2500 inches first end Hub Style Designator:
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches Bore Diameter: 0.3750 inches first end Keyway Width: 0.125 inches both ends Distance From Bore Center To Keyway Bottom: 0.2500 inches first end Hub Style Designator: Plain first end
45.0000 degrees Distance Between Body Face And Protruding Hub End: 0.375 inches first end Face Width: 0.500 inches Bore Diameter: 0.3750 inches first end Keyway Width: 0.125 inches both ends Distance From Bore Center To Keyway Bottom: 0.2500 inches first end Hub Style Designator: Plain first end Hub Diameter:

NSN 3020-00-239-7628

Helical Gear - Page 2 of 2



S	pe	cia	al F	-ea	ıtu	re	S
---	----	-----	------	-----	-----	----	---

Used with processing machine, radiographic film, automatic; 6525-01-138-7492; fscm 19139; part no. 104-2878 w/repair parts

Material:

Plastic polytetrafluoroethylene

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300