## NSN 3020-00-242-9599

Spur Gear - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/3020-00-242-9599

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
2.3750 inches
Teeth Quantity:
76
Bore Style:
W/counterbore both ends
Backlash Designation:
Grade c
Hardness Rating:
28.0 rockwell c and 32.0 rockwell c
Mounting Hole Type And Quantity:
4 plain axially through body, first end
Outside Diameter:
2.4360 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
, c
0.6400 inches first end
0.6400 inches first end
0.6400 inches first end  Face Width:
0.6400 inches first end  Face Width:  0.125 inches
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter:
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth:
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end  Counterbore Diameter:
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end  Counterbore Diameter: 2.1905 inches second end
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end  Counterbore Diameter: 2.1905 inches second end  Hub Style Designator:
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end  Counterbore Diameter: 2.1905 inches second end  Hub Style Designator:  Plain first end
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end  Counterbore Diameter: 2.1905 inches second end  Hub Style Designator:  Plain first end  Hub Diameter:
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end  Counterbore Diameter: 2.1905 inches second end  Hub Style Designator: Plain first end  Hub Diameter: 1.6870 inches first end
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end  Counterbore Diameter: 2.1905 inches second end  Hub Style Designator: Plain first end  Hub Diameter: 1.6870 inches first end  Precision Classification:
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end  Counterbore Diameter: 2.1905 inches second end  Hub Style Designator: Plain first end  Hub Diameter: 1.6870 inches first end  Precision Classification: Quality number 8
0.6400 inches first end  Face Width: 0.125 inches  Bore Diameter: 1.500 inches both ends  Counterbore Depth: 0.0310 inches second end  Counterbore Diameter: 2.1905 inches second end  Hub Style Designator: Plain first end  Hub Diameter: 1.6870 inches first end  Precision Classification: Quality number 8  Mounting Hole Diameter:

## NSN 3020-00-242-9599

Spur Gear - Page 2 of 2



Special Features:
Bore has a 0.058 in. W by 0.040 in. Deep groove located 0.369 in. From face of counterbored end
Material:
Steel comp 416
Material Specification:
Qq-s-764, type 416 cond h federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:

Demilitarization:

Unit Of Measure:

No

N/a

Fiig:

A27300