## NSN 3020-00-242-9743

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-242-9743

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.2501 inches **Teeth Quantity:** 60 **Bore Style:** Tapered w/keyway both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end **Mounting Hole Thread Size:** 0.1120 inches axially through body, first end Mounting Hole Type And Quantity: 3 threaded axially through body, first end **Outside Diameter:** 1.2916 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.3430 inches first end Face Width: 0.1880 inches **Keyway Width:** 0.0940 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.2375 inches first end **Taper Major Diameter:** 0.3503 inches first end Hub Style Designator: Plain first end **Hub Diameter:** 0.6250 inches first end **Bolt Hole Circle Diameter:** 0.844 inches axially through body, first end **Special Features:** Counterbore on second end, 0.563 in. Dia, 0.094 in. Deep Material:

Stainless steel

## NSN 3020-00-242-9743

Spur Gear - Page 2 of 2

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

