NSN 3020-00-246-9983

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-246-9983

Body Style:
Plain, solid
Pitch Diameter:
Between 0.9365 inches and 0.9375 inches
Teeth Quantity:
90
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
0.957 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.219 inches first end
Face Width:
0.187 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.375 inches first end
Precision Classification:
Quality number 10
Special Features:
1 0.040 in. Diameter plain hole and 1 0.112 in. Diameter threaded hole 90.0 degrees apart on hub for positioning
Material:
Steel comp 303
Material Specification:
Qq-s-763, class303 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Protruding hub
Furnished Items And Quantity:
1 setscrew

NSN 3020-00-246-9983

Spur Gear - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300